



## Ceramic Coating Care Sheet

- PLEASE ALLOW 7 FULL DAYS BEFORE WASHING A CERAMIC COATED VEHICLE. THE COATING WILL CONTINUE TO HARDEN DURING THIS TIME, AND IT IS BEST TO NOT SUBMIT THE COATING TO CHEMICALS DURING THIS PERIOD.
- IF THE VEHICLE GETS AN EXCESSIVE AMOUNT OF DIRT, BIRD DROPPINGS, SAP, OR OTHER CONTAMINANTS BEFORE YOU CAN WASH IT, PLEASE CALL ASAP.
- IT IS BEST TO WASH THE VEHICLE WITH QUALITY CAR WASH SOAP, TWO BUCKETS WITH GRIT GUARDS, AND TO DRY WITH MICROFIBER TOWELS AFTER BLOWING MOST WATER OFF WITH A LEAF BLOWER, AIR COMPRESSOR, OR CAR DRYER.
- IF YOU MUST USE AUTOMATIC CAR WASH, BE SURE TO USE A TOUCH FREE WASH. THE TUNNEL WASHES THAT HAVE BRUSHES WILL PUT SCRATCHES INTO EVEN A CERAMIC COATED VEHICLE OVER TIME (AND WILL VOID YOUR IGL COATINGS WARRANTY).



Text/Call (860)335-6258



Like us on Facebook!

[facebook.com/MReflectionsAutoAesthetics](https://www.facebook.com/MReflectionsAutoAesthetics)

[WWW.MREFLECTIONSCT.COM](http://WWW.MREFLECTIONSCT.COM)

